

SUNX DRIVE · EXTERIOR · SENSOR-READY

SUNX Drive XT Series

XT-45 — exterior vertical-screen motor, weather-responsive

The drive for exterior vertical screens and awnings — MERIDIAN and VELARIA. High-speed, with bidirectional wind-and-sun sensor reading so the screen retracts automatically in adverse weather.

TUBE

45 mm Ø

TORQUE

15 Nm

SPEED

30 rpm

RATING

IP44

WHAT IT IS

SUNX Drive XT is built for exterior vertical screens and folding-arm systems. It runs fast (30 rpm) for long façade drops and reads a wind-and-sun sensor over a bidirectional radio link, so the screen closes or retracts to a safe position when the weather turns.

Electronic limits hold position precisely on tall openings, and the solar response can be switched on or off from the handset. Specified for façade-mounted screens facing direct sun and wind exposure.

BUILD

- High-speed 30 rpm
- Bidirectional sensor link
- Encoder positioning
- Electronic limit switches
- Wind-sun safety retract
- Thermal & resistance stop

SPECIFICATION

Model code	XT-45
Tube diameter	45 mm
Torque	15 Nm
Speed	30 rpm
Supply	230 V AC
Power	135 W
Current	0.6 A
Sensor link	Bidirectional · 868.3 MHz
Weather response	Wind + sun, auto-retract
Limit switch	Electronic · encoder
Protection rating	IP44 (higher rating on request)
Control	Radio · open compatibility

